WHAT IS CLAIMED IS:

1. A method of use of a fabric softener composition for the wrinkle recovery treatment or the reduction of wet soiling of textile fibre materials in domestic applications, which softener composition comprises:

A) a fabric softener;

B) at least one additive selected from the group consisting of

a) a polyethylene, or a mixture thereof,

b) a fatty acid alkanolamide, or a mixture thereof,

c) a polysilicic acid, or a mixture thereof, and

d) a polyurethane, or a mixture thereof; and

C) a dispersed polyorganosiloxane of formula (1)

(1)



wherein

$R^1$ is OH, $OR^2$ or $CH_3$

$R^2$ is $CH_3$ or $CH_2CH_3$

$R^3$ is $C_1$-$C_{20}$alkoxy, $CH_3$, $CH_2CHR^4CH_2NHR^5$, or $CH_2CHR^4CH_2N(COCH_3)R^5$

(2)



or (3)

or (4)



$R^4$ is H or $CH_3$

$R^5$ is H, $CH_2CH_2NHR^6$, C(=O)-$R^7$ or $(CH_2)_z$-$CH_3$

z is 0 to 7

$R^6$ is H or C(=O)-$R^7$

$R^7$ is $CH_3$, $CH_2CH_3$ or $CH_2CH_2CH_2OH$

$R^8$ is H or $CH_3$

the sum of X and Y is 40 to 4000;

or a dispersed polyorganosiloxane which comprises at least one unit of the formula (5)

(5) $(R^9)_V (R^{10})_W$ Si-A-B

wherein

$R^9$ is $CH_3$, $CH_3CH_2$ or Phenyl

$R^{10}$ is -O-Si or -O-$R^9$

the sum of v and w equals 3, and v does not equal 3

A = $-CH_2CH(R^{11})(CH_2)_K$

B = $-NR^{12}((CH_2)_l$-$NH)_mR^{12}$, or



(6)

n is 0 or 1

when n is 0, $U^1$ is N, when n is 1, $U^1$ is CH

l is 2 to 8

k is 0 to 6

m is 0 to 3

$R^{11}$ is H or $CH_3$

$R^{12}$ is H, C(=O)-$R^{16}$, $CH_2(CH_2)_pCH_3$ or

(7) 

p is 0 to 6

$R^{13}$ is NH, O, $OCH_2CH(OH)CH_2N(Butyl)$, OOCN(Butyl)

$R^{14}$ is H, linear or branched $C_1$-$C_4$ alkyl, Phenyl or $CH_2CH(OH)CH_3$

$R^{15}$ is H or linear or branched $C_1$-$C_4$ alkyl

$R^{16}$ is $CH_3$, $CH_2CH_3$ or $(CH_2)_qOH$

q is 1 to 6

$U^2$ is N or CH;

or a dispersed polyorganosiloxane of the formula (8)

(8) 

wherein

$R^3$ is as previously defined

$R^{17}$ is OH, $OR^{18}$ or $CH_3$

$R^{18}$ is $CH_3$ or $CH_2CH_3$

$R^{19}$ is $R^{20}$-$(EO)_m$-$(PO)_n$-$R^{21}$

m is 3 to 25

n is 0 to 10

$R^{20}$ is the direct bond or $CH_2CH(R^{22})(CH_2)_pR^{23}$

p is 1 to 4

$R^{21}$ is H, $R^{24}$, $CH_2CH(R^{22})NH_2$ or $CH(R^{22})CH_2NH_2$

$R^{22}$ is H or $CH_3$

$R^{23}$ is O or NH

$R^{24}$ is linear or branched $C_1$-$C_8$ alkyl or $Si(R^{25})_3$

$R^{25}$ is $R^{24}$, $OCH_3$ or $OCH_2CH_3$

EO is $-CH_2CH_2O-$

PO is $-CH(CH_3)CH_2O-$ or $-CH_2CH(CH_3)O-$

the sum of $X_1$,$Y_1$ and S is 20 to 1500;

or a dispersed polyorganosiloxane of the formula (9)

(9) 

wherein

$R^{26}$ is linear or branched $C_1$ - $C_{20}$ alkoxy, $CH_2CH(R^4)R^{29}$

$R^4$ is as previously defined

$R^{29}$ is linear or branched $C_1$ - $C_{20}$ alkyl

$R^{27}$ is aryl, aryl substituted by linear or branched $C_1$ - $C_{10}$ alkyl, linear or branched $C_1$ - $C_{20}$ alkyl substituted by aryl or aryl substituted by linear or branched $C_1$ - $C_{10}$ alkyl

$R^{28}$ is

(10) 

the sum of $X^2$, $X^3$, $X^4$ and $Y^2$ is 20 to 1500, wherein $X^3$, $X^4$ and $Y^2$ may be independently of each other 0;

or a mixture thereof.

2. A method of use according to claim 1 wherein the polyorganosiloxane is of formula (1):

(1) 

wherein

$R^1$ is OH, $OR^2$ or $CH_3$

$R^2$ is $CH_3$ or $CH_2CH_3$

$R^3$ is $C_1$-$C_{20}$alkoxy, $CH_3$, $CH_2CHR^4CH_2NHR^5$, or

(2) 

or (3) 

$R^4$ is H or $CH_3$

$R^5$ is H, $CH_2CH_2NHR^6$, $C(=O)$-$R^7$

$R^6$ is H or $C(=O)$-$R^7$

$R^7$ is $CH_3$, $CH_2CH_3$ or $CH_2CH_2CH_2OH$

$R^8$ is H or $CH_3$

the sum of X and Y is 40 to 1500

or a dispersed polyorganosiloxane which comprises at least one unit of the formula (5);

(5) $(R^9)_V (R^{10})_W$ Si-A-B

wherein

$R^9$ is $CH_3$,

$R^{10}$ is -O-Si or -O-$R^9$

the sum of v and w equals 3, and v does not equal 3

A = $-CH_2CH(R^{11})(CH_2)_K$

B =

(6) 

n is 1

$U^1$ is CH

k is 0 to 6

$R^{11}$ is H or $CH_3$

$R^{13}$ is OOCN(Butyl)

$R^{14}$ is H, linear $C_1$-$C_4$ alkyl, Phenyl

$R^{15}$ is H or linear $C_1$-$C_4$ alkyl

$U^2$ is N

or a dispersed polyorganosiloxane of the formula (8);

(8)



wherein

$R^3$ is as previously defined

$R^{17}$ is OH, $OR^{18}$ or $CH_3$

$R^{18}$ is $CH_3$ or $CH_2CH_3$

$R^{19}$ is $R^{20}$-$(EO)_m$-$(PO)_n$-$R^{21}$

m is 3 to 25

n is 0 to 10

$R^{20}$ is the direct bond or $CH_2CH(R^{22})(CH_2)_pR^{23}$

p is 1 to 4

$R^{21}$ is H, $R^{24}$, $CH_2CH(R^{22})NH_2$ or $CH(R^{22})CH_2NH_2$

$R^{22}$ is H or $CH_3$

$R^{23}$ is O or NH

$R^{24}$ is linear or branched $C_1$-$C_3$ alkyl or $Si(R^{25})_3$

$R^{25}$ is $R^{24}$, $OCH_3$ or $OCH_2CH_3$

EO is $-CH_2CH_2O-$

PO is $-CH(CH_3)CH_2O-$ or $-CH_2CH(CH_3)O-$

the sum of $X_1$, $Y_1$ and s is 40 to 1500

or a dispersed polyorganosiloxane of the formula (9);

(9) 

$R^{26}$ is linear $C_1$ - $C_{20}$ alkoxy, $CH_2CH(R^4)R^{29}$

$R^4$ is as previously defined

$R^{29}$ is linear $C_1$ - $C_{20}$ alkyl

$R^{27}$ is, $CH_2CH(R^4)$Phenyl

$R^{28}$ is

(10) 

the sum of $X^2$, $X^3$, $X^4$ and $Y^2$ is 40 to 1500, wherein $X^3$, $X^4$ and $Y^2$ may be independently of each other 0;

or a mixture thereof.

3. A method of use according to claim 1 or 2 wherein a polyorganosiloxane of formula (1) is used, wherein

$R^1$ is OH or $CH_3$,

$R^3$ is $CH_3$, $C_{10}$-$C_{20}$alkoxy or $CH_2CHR^4CH_2NHR^5$,

$R^4$ is H,

$R^5$ is H or $CH_2CH_2NHR^6$,

$R^6$ is H or C(=O)-$R^7$, and

$R^7$ is $CH_3$, $CH_2CH_3$ or especially $CH_2CH_2CH_2OH$.

4. A method of use according to claim 1 or 2 wherein a polyorganosiloxane of formula (8) is used, wherein

$R^3$ is $CH_3$, $C_{10}$-$C_{20}$alkoxy or $CH_2CHR^4CH_2NHR^5$,

$R^4$ is H,

$R^5$ is H or $CH_2CH_2NHR^6$,
$R^6$ is H or C(=O)-$R^7$,
$R^7$ is $CH_2CH_3$, $CH_2CH_2CH_2OH$ or especially $CH_3$, and
$R_{17}$ is $CH_3$ or OH.

5. A method of use according to claim 1 or 2 wherein a polyorganosiloxane of formula (9) is used, wherein
$R^{26}$ is $CH_2CH(R^4)R^{29}$,
$R^4$ is H, and
$R^{27}$ is 2-phenyl propyl.

6. A method of use according to any of claims 1 to 5 wherein the composition is a liquid aqueous composition.

7. A method of use according to any of claims 1 to 6 wherein the composition is used in a tumble dryer sheet composition.

8. A method of use according to any of claims 1 to 7 in which the polyorganosiloxane is nonionic or cationic.

9. A method of use according to any of claims 1 to 8 in which the composition has a solids content of 5 to 70 % at a temperature of 120°C.

10. A method of use according to any of claims 1 to 9 in which the composition contains a water content of 25 to 90 % by weight based on the total weight of the composition.

11. A method of use according to any of claims 1 to 10 in which the composition has a pH value from 2 to 7.

12. A method of use according to any of claims 1 to 11 in which the nitrogen content of the aqueous emulsion due to the polyorganosiloxane is from 0 to 0.25 % with respect to the silicon content.

13. A method of use according to any of claims 1 to 12 wherein the composition comprises a polyethylene, a fatty acid alkanolamide or a polyurethane.

14. A method of use according to any of claims 1 to 13 wherein the composition comprises a polyethylene or a fatty acid alkanolamide.

15. A method of use according to any of claims 1 to 14 wherein the composition comprises a fatty acid alkanolamide.

16. A method of use according to any of claims 1 to 14 wherein the composition comprises a polyethylene.

17. A method of use according to any of claims 1 to 16 wherein the composition is prepared by mixing a preformulated fabric softener with an emulsion comprising the polyorganosiloxane and the additive.

18. A method of use according to any of claims 1 to 17 wherein composition has a clear appearance.

19. A method of use according to any of claims 1 to 18 in which the composition comprises:
a) 0.01 to 70 % by weight, based on the total weight of the composition, of a polyorganosiloxane, or a mixture thereof;
b) 0.2 to 25 % by weight based on the total weight of an emulsifier, or a mixture thereof;
c) 0.01 to 15 % by weight based on the total weight of at least one additive selected from the group consisting of a polyethylene, a fatty acid alkanolamide, a polysilicic acid and a polyurethane, and
d) water to 100 %.

20. A tumble dryer sheet comprising a composition as defined in claim 1.